

# IGLAND 60

<http://www.igland-as.com/en/skog/igland-60/>

Powerful one-drum forest winch for those in need of a powerful and reliable winch. IGLAND 60 has an unusually large drum capacity to provide space for wide range of wire rope with sufficient length. Rugged and simple design with large logging plate provides excellent ground support. The winch is equipped with a double clutch for greater reliability, less wear and longer lifespan. Available with Pullmatic (hydraulic output of rope) as an option.

## IGLAND 60

- **Pulling capacity 60 kN (6 tons)**
- **Ideal for tractors 45 to 75 kW (60 – 100 hp)**
- **Automatic safety brake**
- **Mechanical control**
- **3-point hitch as standard**
- **Weight 390 kg**
- **Logging plate width 1,73 meters**
- **Cableguard prevents derailment**
- **Radio control is optional**
- **Ratio 1:6**
- **Double clutch**
- **Adjustable height of pulling point**

## Technical data

Max pulling capacity / empty drum:	60 kN (6 tonn)
Max pulling capacity / full drum:	26 kN (2,6 tons)
Number of drums:	1
Wire rope, theoretical capacity:	128 m,10 mm/ 103 m,11 mm/ 85 m,12 mm
Recommended wire rope length:	50 m, 11 mm
Pulling speed at 540 rpm:	u/gir: 0,76 - 1,73 m/s, m/gir: 0,44 – 1,00 m/s
Ratio:	u/gir: 1:6, m/gir: 1:10,36
Necessary power input:	u/gir: 49 kW , m/gir: 31 kW
Braking power:	Min 75 kN (7,5 tons)
Controls:	Standard cord operation
Clutch:	Replaceable friction pads
Brake:	Automatic safety brake

Mounting:

PTO input, distance from ground:

Height/ Width/ Depth:

Weight (without wire rope):

3-point hitch

50 cm

198/ 173/ 70 cm

390 kg

