

## PackFix Hydro

Drying, storing and delivering of firewood in the perfect packaging

- For billets with a length of up to 50 cm
- Available in 3 versions:  
Stationary / Mobile / Multi-purpose
- Filling drum volume:  
1.63 m³ = 1.6 loose cubic metres =  
1.0 cubic metres of timber
- Filling drum: 120 cm, height 145 cm  
with quick-change system



### PackFix Hydro Stationary

Only unit can be transported.  
Height-adjustable subframe as standard. Flat area required.

Article no.	Type	Drive	Weight kg	
M7355S	E3-400 <sup>❶</sup> 3x 400V, 50Hz	3 kW e-motor 400 V, S6, CEE 16A, stationary model without three-point linkage	~ 634	
M7357S	E3-230 <sup>❶</sup> 230V, 50Hz	3 kW e-motor 230 V, S6, stationary model without three-point linkage	~ 628	
M7350S	PS <sup>❷</sup>	Tractor hydraulics, max. pump delivery rate 10 l/min, max. 150 bar, size 3 hydraulic plug, stationary model without three-point linkage	~ 590	
M7351	PZ <sup>❸</sup>	Attachable PTO pump max. 430 rpm	~ 625	
M7360S	B3,1	3.1 kW petrol engine, consumption: 0.5–0.7 l/h, tank capacity: 1 l, stationary model without three-point linkage	~ 640	

### Special equipment PackFix Hydro Stationary

Valid for initial equipment, incl. assembly.

Article no.	Namer	Weight kg	
TH	Tilting table incl. second filling drum with hydraulic drive from control panel, incl. installation (instead of standard base frame only for stationary operation)	~ 540	
X	Surcharge for 30 cm higher drum with volume of 2 loose m³ (machine height + 60 cm) for PackFix Hydro	~ 60	
GH	Floor frame for charging with pallet truck instead of standard base frame. Level ground required for PackFix Hydro Stationary and Universal	~ 30	

❶ E-drive: with motor circuit breaker and phase inverter    ❷ Tractor drive    ❸ Tractor drive: Universal joint shaft required

## PackFix Hydro Mobile

Can only be operated via three-point, unit and log bundles can be transported together, tractor necessary for operation. Pallet fork as standard.

Article no.	Type	Article no.	Weight kg	
M7340M <sup>❶</sup>	PS	Tractor hydraulics, max. pump delivery rate 10 l/min, max. 150 bar, size 3 hydraulic plug, with three-point linkage and pallet fork	~ 548	
M7341M <sup>❶</sup>	PZ	Attachable PTO pump max. 430 rpm, with three-point linkage and pallet fork	~ 538	

### Special equipment PackFix Hydro Mobil

Valid for initial equipment, incl. assembly.

Article no.	Name	Weight kg	
GH	Floor frame for charging with pallet truck instead of standard base frame. Level ground required	~40	
UR	Adjustable base frame instead of standard pallet fork. Level ground required	~ 0	

### PackFix Hydro Universal

Unit and log bundles can be transported, operation without tractor possible.  
Height-adjustable subframe and pallet fork as standard.  
Flat area required.

Article no.	Type	Drive	Weight kg	
M7344	PZE3-400 <sup>❶❷❸</sup> 3x 400V, 50Hz	• Attachable PTO drive max. 430 rpm • 3 kW e-motor 400V, S6, CEE 16A	~ 738	

### Special equipment PackFix Hydro Universal

Valid for initial equipment, incl. assembly.

Article no.	Name	Weight kg	
GH without surcharge	Floor frame for charging with pallet truck instead of standard base frame. Level ground required for PackFix Hydro Stationary and Universal	~30	