



583

The 583 is our longest reaching loader. This model incorporates a telescopic double extension, taking the reach to 8 metres.

The 583 gives additional flexibility when feeding a chipper or working where long reach is an advantage.

It is ideally suited for those who require a unit mounted on the roof of their Valtra tractor.



The 573 is fast becoming the most popular loader in the Botex heavy duty range.

It delivers the same heavyduty lift as the 560, with the added benefit of additional reach.

This loader will comfortably load a trailer capable of carrying two bays of 3m timber. This loader is fitted to our XL PRO-14 and GR-15 trailers as standard.



560

The first in our range of heavy-duty loaders.

This has been the best selling loader in the Botex range for many years.

This loader is mounted to our Euro-11 trailer as standard, and is a popular option for roof mounting onto Valtra tractors.



360

The 360 is our entry level loader which can be supplied with or without 3-point linkage mounting.

This loader is powered by the tractor's hydraulics, and as such the tractor's PTO is left accessible to allow other machinery to run.

This loader is generally fitted to our Eco-8 or GR-8 trailers or sold in conjunction with a crane fed chipper.

Specification	583	573	560	360
Max. Reach (Metres)	8.3	7.3	6	6
Boom Extension (Metres)	3.3	1.5	1.3	1.3
Lift Capacity, Close-In (kg)	2200	2300	2000	1000
Lift Capacity, at 4 Metres (kg)	1100	1200	1120	600
Lift Capacity, at Full Reach (kg)	530	630	700	400
Slewing Angle	370°	370°	370°	370°
Rotator Type	6 T	6 T	6 T	3 T
Grapple Opening (cm)	145	145	145	111

Loader Controls

SLEWING TORQUE: 18.5 KNM LIFTING FORCE: 65 KNM

Whatever your application, we have a range of controls available to suit your requirements. Our in-house team can provide the best suited control system to link your base machine with your chosen loader.







