

HydroCombi 10/13

V2 Speed

The entry-level hydraulic firewood splitters.

- **Fixomatic system** as a standard
- **Grey cast iron pump** as standard
- **Max. billet length** 110 cm
- **Splitting knife length** 24 cm
- **Cylinder stroke** 100 cm
- **Tank capacity** 18l hydraulic oil
- **Dimensions storage area** approx. 135 × 120 cm
- **Height transport position** 193 cm
- **Height work position** 255 cm
- **Special equipment:**
Autospeed, three-point linkage, chassis
- **Construction according to latest standard EN 609-1**



HydroCombi 10 PS-V2
work position

HydroCombi 13 PZG
with driving device (F0003117)

HydroCombi 10

Hydraulic, entry-level firewood splitter for metre-long logs with standard 2 forward speeds.

| Article no. | Type | Drive | Max. punching speed cm/s Forward movement stage 1/2 return movement | | Splitting power t | Weight kg |
|-------------|-----------------------------|--|---|----------|----------------------|--------------|
| M2832M | PZG-V2 ^① | Tractor PTO shaft, power consumption 11 kW, oil pump with max. capacity 27 l/min built-in, recommended PTO shaft speed 300-380 rpm | 12 / 28 | 20 | 10 | ~ 334 |
| M2830M | E5,5-V2 ^② | 5.5 kW e-motor 400V, S6, CEE 16A, manual chassis with support wheel | 6 / 15 | 10 | 10 | ~ 342 |
| M2831M | E5,5D-V2 Turbo ^③ | 5.5 kW e-motor 400V, S6, CEE 16A, dual-stage pump, manual chassis with support wheel | 5 / 32 | 23 | 10 | ~ 354 |
| M2839M | E3D-V2 ^③ | 3 kW e-motor 230V, S6, dual-stage pump, manual chassis with support wheel | 2 / 18 | 13 | 9 | ~ 345 |
| M2834M | PZG-E5,5-V2 ^{①②} | · Tractor, power consumption 11 kW · 5.5 kW E-motor 400V, S6, CEE 16A | 12 / 28 6 / 15 | 20 10 | 10 | ~ 382 |
| M2838M | PS-V2 ^② | Tractor hydraulics, hydraulic sleeve 3 for forward and return movement. Non-pressurised return movement required! Compl. with connection tubes and hydraulic plug. Max. delivery rate of pump 16 l/min | 7 / 17 | 12 | 10 | ~ 310 |
| M2837M | B5,5D-V2 Turbo | 5.5 kW petrol engine (B&S), dual-stage pump, consumption: 1.0-1.5 l/h, tank capacity: 4.1 l, manual chassis with support wheel | 4 / 32 | 23 | 10 | ~ 344 |

^① Tractor drive: universal shaft required, three-point linkage cat. I+II

^② Tractor drive: three-point linkage cat. I+II

^③ E-drive: with motor circuit breaker and phase inverter

HydroCombi 13

Hydraulic, entry-level firewood splitter for metre-long logs with 2 advance speeds and more splitting power as a standard.

| Article no. | Type | Drive | Max. punching speed cm/s Forward movement stage 1/2 return movement | | Splitting power t | Weight kg |
|-------------|-----------------------------|---|---|---------|----------------------|--------------|
| M2822M | PZG-V2 ^① | Tractor PTO shaft, power consumption 14 kW, oil pump with max. capacity 32 l/min-built-in, recommended PTO shaft speed 300-450 rpm | 11 / 23 | 20 | 13 | ~ 356 |
| M2820M | E5,5-V2 ^② | 5.5 kW e-motor 400V, S6, CEE 16A, manual chassis with support wheel | 5 / 10 | 9 | 13 | ~ 354 |
| M2821M | E5,5D-V2 Turbo ^③ | 5.5 kW e-motor 400V, S6, CEE 16A, dual-stage pump, manual chassis with support wheel | 4 / 22 | 19 | 13 | ~ 362 |
| M2829M | E3D-V2 ^③ | 3 kW e-motor 230V, S6, dual-stage pump, manual chassis with support wheel | 2 / 12 | 11 | 12 | ~ 355 |
| M2824M | PZG-E5,5-V2 ^{①②} | · Tractor, power consumption 14 kW · 5.5 kW E-motor 400V, S6, CEE 16A | 11 / 23 5 / 10 | 28 9 | 13 | ~ 386 |
| M2828M | PS-V2 ^② | Tractor hydraulics, hydraulic sleeve 3 for forward and return movement required. Compl. with connection tubes and hydraulic plug. Non-pressurised return movement required! Max. delivery rate of pump 30 l/min | 10 / 21 | 19 | 13 | ~ 318 |
| M2823M | B5,5D-V2 Turbo | 5.5 kW petrol engine (B&S), dual-stage pump, consumption: 1.0-1.5 l/h, tank capacity: 4.1, with manual chassis | 3 / 22 | 19 | 13 | ~ 354 |
| M2826M | B9,7-V2 | 9.7 kW petrol engine (B&S), consumption: 2.0-2.5 l/h, tank capacity: 8.5 l with manual chassis | 6 / 12 | 11 | 13 | ~ 370 |

Special equipment HydroCombi 10/13

Valid for initial equipment, incl. assembly.

| Article no. | Name |
|-------------|---|
| R | AUTOSPEED for pressure-controlled switching between the feed speeds. |
| D | Three-point linkage for transporting machines with E-drive, incl. driving device (F0003117) |

Accessory equipment HydroCombi 10/13

| Article no. | Name |
|-------------|--|
| F0003186 | Attachable floor grid, anti-slip |
| F0003117 | Driving device for PS/PZG/PZG-E drive |
| Z2000635 | Walterscheid W-Line universal shaft |
| F0003357 | Power saw bracket: Safe transportation and handy storage for the power saw |
| F0001482 | Hour counter for machines with petrol engine |
| F0002179 | Hour counter for machines with E-drive |
| F0001806 | Hour counter for machines with PTO drive, includes rpm display |